




DRAGSTER 800 ROSSO



AGO RED/METALLIC CARBON BLACK



* Top speed attained on closed course.
** Limited power versions available on demand.
*** Available with and without EAS for the European market; only with EAS for the Extra European market
Every country could have a price variation due to local import duties and taxes.

ENGINE

Type Three cylinder, 4 stroke, 12 valve
Timing system "D.O.H.C" with mechanical chain tensioner
Total displacement 798 cm³ (48.68 cu. in.)
Compression ratio 12.3:1
Starting Electric

Bore x stroke 79 mm x 54.3 mm (3.1 in. x 2.1 in.)
Max. power - r.p.m. (at the crankshaft)** 81 kW (110 hp) at 11.500 r.p.m.

Max. torque - r.p.m. 83 Nm (8.46 kgm) at 7.600 r.p.m.
Cooling system Cooling with separated liquid and oil radiators

Engine management system Integrated ignition - injection system MVICS 2.0 (Motor & Vehicle Integrated Control System) with three injectors. Engine control unit Eldor EM2.0, throttle body full ride by wire Mikuni, pencil-coil. Torque control with four maps, Traction Control with eight levels of intervention.

Electronic quick-shift MV EAS 2.1 (Electronically Assisted Shift up & down)***

Clutch Multi-disk wet clutch with hydraulic actuation and back torque limiting device

Transmission Cassette style; six speed, constant mesh
Primary drive 22/41

Gear ratio
First gear: 13/37
Second gear: 16/35
Third gear: 18/32
Fourth gear: 20/30
Fifth gear: 22/29
Sixth gear: 21/25
Final drive ratio 16/41

ELECTRICAL EQUIPMENT

Voltage 12 V
Alternator 350 W at 5000 r.p.m.
Battery 12 V - 8.5 Ah

DIMENSIONS AND WEIGHT

Wheelbase 1400 mm (55,12 in.)
Overall length 2035 mm (80,12 in.)
Overall width 935 mm (36,81 in.)
Saddle height 845 mm (33,27 in.)
Min. ground clearance 135 mm (5,31 in.)
Trail 103,5 mm (4,07 in.)
Dry weight 168 kg (370,38 lbs.)
Fuel tank capacity 16,5 l (4,36 U.S. gal.)

PERFORMANCE

Maximum speed* 237.0 km/h (147.2 mph)

FRAME

Type ALS Steel tubular trellis
Rear swing arm pivot plates material Aluminium alloy

FRONT SUSPENSION

Type Marzocchi "UPSIDE DOWN" telescopic hydraulic fork with rebound-compression damping and spring preload external and separate adjustment
Fork dia. 43 mm (1.69 in.)
Fork travel 125 mm (4.92 in.)

REAR SUSPENSION

Type Progressive Sachs, single shock absorber with rebound and compression damping and spring preload adjustment
Single sided swing arm material Aluminium alloy
Wheel travel 124 mm (4.88 in.)

BRAKES

Front brake Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking disc and flange
Front brake caliper Brembo radial-type, with 4 pistons Ø 32 mm (Ø 1.26 in.)
Rear brake Single steel disc with Ø 220 mm (Ø 8.66 in.) dia.
Rear brake caliper Brembo with 2 pistons - Ø 34 mm (Ø 1.34 in.)
ABS System Bosch 9 Plus with RLM (Rear wheel Lift-up Mitigation)

WHEELS

Front: Material/size Aluminium alloy 3.50 " x 17 "
Rear: Material/size Aluminium alloy 6.00 " x 17 "

TYRES

Front 120/70 - ZR 17 M/C (58 W)
Rear 200/55 - ZR 17 M/C (75 W)

FAIRING

Material Thermoplastic

CONTENTS

Exclusive contents Immobilizer

EMISSIONS

Environmental Standard Euro 4
Combined fuel consumption 5.6 l/100 km
CO₂ Emissions 128 g/km